## **Environmental Protection Agency**

## TABLE 35 TO SUBPART G OF PART 63—CONTROL REQUIREMENTS FOR ITEMS OF EQUIPMENT THAT MEET THE CRITERIA OF §63.149 OF SUBPART G

Item of equipment	Control requirement <sup>a</sup>
Drain or drain hub	(a) Tightly fitting solid cover (TFSC); or (b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meet-
Manhole <sup>b</sup>	ing the requirements of § 63.139(c); or (c) Water seal with submerged discharge or barrier to protect discharge from wind. (a) TFSC; or
	(b) TSFC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of §63.139(c); or
Lift station	(c) If the item is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside diameter. (a) TFSC; or
	(b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of §63.139(c); or
	(c) If the lift station is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside di- ameter. The lift station shall be level controlled to minimize changes in the liquid level.
Trench	<ul><li>(a) TFSC; or</li><li>(b) TFSC with a vent to either a process, or to a fuel gas system, or to a control device meeting the requirements of §63.139(c); or</li></ul>
	(c) If the item is vented to the atmosphere, use a TFSC with a properly operating water seal at the entrance or exit to the item to restrict ventilation in the collection system. The vent pipe shall be at least 90 cm in length and not exceeding 10.2 cm in nominal inside diameter.
Pipe	Each pipe shall have no visible gaps in joints, seals, or other emission interfaces.
Oil/Water separator	<ul> <li>(a) Equip with a fixed roof and route vapors to a process or to a fuel gas system, or equip with a closed vent system that routes vapors to a control device meeting the requirements of §63.139(c); or</li> </ul>
	(b) Equip with a floating roof that meets the equipment specifications of §60.693 (a)(1)(i), (a)(1)(ii), (a)(2), (a)(3), and (a)(4).
Tank <sup>c</sup>	Maintain a fixed roof. d If the tank is sparged or used for heating or treating by means of an exothermic reaction, a fixed roof and a system shall be maintained that routes the organic hazardous air pollutants vapors to other process equipment or a fuel gas system, or a closed vent system that routes vapors to a control device that meets the requirements of 40 CFR §63.119 (e)(1) or (e)(2).

a Where a tightly fitting solid cover is required, it shall be maintained with no visible gaps or openings, except during periods of sampling, inspection, or maintenance.
 b Manhole includes sumps and other points of access to a conveyance system.
 c Applies to tanks with capacities of 38 m³ or greater.
 d A fixed roof may have openings necessary for proper venting of the tank, such as pressure/vacuum vent, j-pipe vent.
 The liquid in the tank is agitated by injecting compressed air or gas.

TABLE 36 TO SUBPART G OF PART 63—COMPOUND LISTS USED FOR COMPLIANCE DEM-ONSTRATIONS FOR ENHANCED BIOLOGICAL TREATMENT PROCESSES (SEE  $\S63.145(h)$ 

List 1	List 2	
Acetonitrile	Acetaldehyde.	
Acetophenone	Acrolein.	
Acrylonitrile	Allyl Chloride.	
Biphenyl	Benzene.	
Chlorobenzene	Benzyl Chloride,	
Dichloroethyl Ether	Bromoform.	
Diethyl Sulfate	Bromomethane.	
Dimethyl Sulfate	Butadiene 1,3.	
Dimethyl Hydrazine 1,1	Carbon Disulfide.	
Dinitrophenol 2,4	Carbon Tetrachloride	
Dinitrotoluene 2,4	Chloroethane (ethyl chloride).	
Dioxane 1,4	Chloroform.	
Ethylene Glycol Monobutyl	Chloroprene.	
Ether Acetate		
Ethylene Glycol Monomethyl	Cumene (isopropylbenzene).	
Ether Acetate		
Ethylene Glycol Dimethyl Ether	Dibromoethane 1,2.	
Hexachlorobenzene	Dichlorobenzene 1,4.	
Isophorone	Dichloroethane 1,2.	
Methanol	Dichloroethane 1,1 (ethylidene dichloride).	
Methyl Methacrylate	Dichloroethene 1,1 (vinylidene chloride).	
Nitrobenzene	Dichloropropane 1,2.	
Toluidine	Dichloropropene 1,3.	

## 40 CFR Ch. I (7-1-14 Edition)

## Pt. 63, Subpt. G, Table 37

List 1	List 2
Trichlorobenzene 1,2,4	Dimethylaniline N,N. Epichlorohydrin. Ethyl Acrylate. Ethylene Oxide. Ethylene Oxide. Ethylene Dibromide. Hexachlorobutadiene. Hexachlorobutadiene. Hexane-n. Methyl Isobutyl Ketone. Methyl Teritary Butyl Ether. Methyl Chloride. Methyl Chloride (dichloromethane). Naphthalene. Nitropropane 2 Phosgene. Propionaldehyde. Propylene Oxide. Styrene. Tetrachloroethane 1,1,2,2. TolueneTrichloroethane 1,1,1 (methyl chloroform). Trichloroethane 1,1,2. Trichloroethylene. Trimethylpentane 2,2,4. Vinyl Chloride. Vinyl Acetate. Xylene-m. Xylene-o. Xylene-o. Xylene-p.

 $[59\;\mathrm{FR}\;19468,\,\mathrm{Apr.}\;22,\,1994,\,\mathrm{as}\;\mathrm{amended}\;\mathrm{at}\;71\;\mathrm{FR}\;76615,\,\mathrm{Dec.}\;21,\,2006]$ 

Table 37 to Subpart G of Part 63—Default Biorates for List 1 Compounds

Compound name	
Acetonitrile	0.100
Acetophenone	0.538
Acrylonitrile	0.750
Biphenyl	5.643
Chlorobenzene	10.000
Dichloroethyl ether	0.246
Diethyl sulfate	0.105
Dimethyl hydrazine(1,1)	0.227
DIMethyl sulfate	0.178
Dinitrophenol 2,4	0.620
Dinitrotoluene(2,4)	0.784
Dioxane(1,4)	0.393
Ethylene glycol dimethyl ether	0.364
Ethylene glycol monomethyl ether acetate	0.159
Ethylene glycol monobutyl ether acetate	0.496
Hexachlorobenzene	16.179
ISophorone	0.598
Methanol	0.200
Methyl methacrylate	4.300
Nitrobenzene	2.300
Toluidine (-0)	0.859
Trichlorobenzene 1,2,4	4.393
Trichlorophenol 2,4,5	
Triethylamine	1.064